

Mission:

To protect, promote & improve the health of all people in Florida through integrated state, county & community efforts.



Rick Scott
Governor

Celeste Philip, MD, MPH
Surgeon General and Secretary

Vision: To be the Healthiest State in the Nation

MEMORANDUM

INFORMATION
DCEH 2017-007

DATE: October 20, 2017

TO: County Health Department Directors/Administrators
ATTN: Environmental Health and Engineering Directors

THROUGH: Kendra F. Goff, PhD, DABT, CPM, CEHP, State Toxicologist and Chief
Bureau of Environmental Health *[Signature]*

FROM: Ed Barranco, MPH, CEHP, CPM, Environmental Administrator
Bureau of Environmental Health, Onsite Sewage Programs *[Signature]*

SUBJECT: ANSI/NSF Standard 40 Aerobic Treatment Unit, Bio-Microbics BioBarrier (new listing)

INFORMATION ONLY

The Bio-Microbics, Inc., BioBarrier® Aerobic Treatment Unit (ATU) with the models BioBarrier MBR 0.5, BioBarrier MBR 0.5-N, BioBarrier MBR 1.0, BioBarrier MBR 1.0-N, BioBarrier MBR 1.5, and BioBarrier MBR 1.5-N has been certified as meeting all the requirements of ANSI/NSF Standard 40 - Residential Wastewater Treatment Systems for Class I classification. Models based on Wastewater Technology Evaluation Report 10/06/055/0030 have been added to the listing of ATUs acceptable for use in the State of Florida.

The following table lists the models, the required compartment sizes and hydraulic treatment capacity. The models can be installed in single tanks, which shall receive distinct approval numbers after review and approval as treatment receptacles before installation. Tanks for the combined 2nd and 3rd compartments of the "-N" model series shall receive distinct approval numbers after review and approval as treatment receptacles before installation.

Unit	Compartment (one or two tanks)	1 st Compartment minimum size (gal)	2 nd (and 3 rd) Compartment combined minimum size (gal)	Hydraulic Treatment Capacity (gpd)
BioBarrier MBR 0.5	2	365	1135	500
BioBarrier MBR 1.0	2	730	2270	1000
BioBarrier MBR 1.5	2	1095	3405	1500
BioBarrier MBR 0.5-N	3	365	1135	500
BioBarrier MBR 1.0-N	3	730	2270	1000
BioBarrier MBR 1.5-N	3	1095	3405	1500

Florida Department of Health

Division of Disease Control & Health Protection • Bureau of Environmental Health
4052 Bald Cypress Way, Bin A-08 • Tallahassee, FL 32399-1710
PHONE: 850/245-4250 • FAX: 850/487-0864

FloridaHealth.gov



Accredited Health Department
Public Health Accreditation Board

Two-tank installations for the two-compartment BioBarrier MBR 0.5, 1.0, and 1.5 models may use already approved single compartment tanks, provided Bio-Microbics concurs with their use and they meet the volume and dimensional requirements and restrictions below:

Additional restrictions based on Bio-Microbics instructions and NSF-40 certification:

- If a two-tank installation, the first tank shall have a minimum 38.25 inches' liquid level to fit the filter.
- If a single-tank installation, the flow-through hole between the first and the second compartment tank shall have an invert at least 47 inches high to fit the filter and to allow operation of the membrane unit. The invert of the flow-through hole shall be at least as high as the maximum operating level in the compartment containing the membrane unit.
- If the first compartment is not a separate tank, the first compartment wall in a three-compartment installation must go to the top of the tank and must be sealed to the lid in accordance with Rule 64E-6.013(2)(i), Florida Administrative Code. The second compartment wall does not need to reach the top of the tank and must reach to the maximum operating water level.
- Operating water level in the compartment containing the membrane unit shall be limited by floats set to a minimum of 36 inches and a maximum of 47 inches. This may vary some, for particular tank configurations, if approved by Bio-Microbics.
- Discharge point of pump line shall be a maximum of eight feet above bottom of the tank.
- Levelness of tank for 2nd (and 3rd) compartment must be within ¼ inch from inlet to outlet and side to side.
- NSF International has allowed the use of a coarse bubbler with specifications provided by Bio-Microbics instead of a mixing pump in the second of a three-compartment installation.

Enclosed, you will find electronic copies of the performance testing and evaluation certification report conducted by NSF International as well as an operation and maintenance manual.

Please direct any questions to Eberhard Roeder at (850) 901-6512.

Enclosures

cc: Bio-Microbics, Inc.



BioBarrier[®] Owner's Manual

FOR USE WITH

NSF/ANSI Std. 40 Class I / 245 / 350 Class R
BioBarrier[®] 0.5, 1.0, 1.5, 0.5-N, 1.0-N, and 1.5-N

NSF/ANSI Std. 245 Class R
BioBarrier[®] 0.5-N, 1.0-N, and 1.5-N



BioBarrier Owner's Manual © 2016 Bio-Microbics, Inc. Revised February 2016.
BioBarrier is registered trademarks owned by Bio-Microbics, Inc.
Other trademarks used are registered by their respective owners.

OWNER'S MANUAL

GENERAL INFORMATION

The BioBarrier® 0.5, 0.5-N, 1.0, 1.0-N, 1.5 & 1.5-N membrane bioreactor wastewater treatment systems are certified by the NSF International/ American National Standards Institute Organizations for wastewater treatment. All BioBarrier® products are ETL certified for safety (electrical, environmental, etc.). If you have questions regarding any Bio-Microbics products please contact us at:

800-753-FAST (3278) or (913) 422-0707

e-mail: onsite@biomicrobics.com

Dear BioBarrier® System Owner

Congratulations! You have a BioBarrier® membrane bioreactor wastewater treatment system installed on your property.

At the forefront of green technology, the BioBarrier® System by Bio-Microbics meets the highest industry treatment standards. Based on environmentally sound and simple scientific principles, the BioBarrier® process is our continued commitment to improve small onsite treatment capabilities. You can take pride in knowing that, with the BioBarrier® system, you will help ensure a clean environment for future generations.


Please take time to read this BioBarrier® Owner's Manual, you will learn important safety precautions, review detailed information on proper use and care of your system. Designed for minimal operator attention, the BioBarrier® System is designed for the simplicity that the onsite wastewater market requires. By consistently following a maintenance schedule and being mindful of what can go down your drains, you can enjoy the lasting benefits of the BioBarrier® membrane bioreactor wastewater treatment system for decades to come.

If you should desire any further assistance, please contact Bio-Microbics at sales@biomicrobics.com or call us at 800-753-3278.

Thank you again for using BioBarrier®!

Sincerely,

Bio-Microbics Team




Top things you can do to prolong the life of your system:

1. Have the BioBarrier® system inspected and tank pumped as necessary.
2. Keep track of the substances entering your system, please review the list of Do's & Don'ts
3. Keep the BioBarrier® System operating - do not turn off the blower.
4. Care for your drain field or irrigation system (if incorporated into your BioBarrier® System).

THE BIOBARRIER® SYSTEM

The BioBarrier® System, is a membrane bioreactor providing primary settling, fecal coliform, BOD, TSS and nitrogen reduction (if needed) using aeration and anoxic zones, and membrane filtration. The system is contained in locally supplied tanks, either in a two or three compartment tank, or multiple tanks, with the membrane module always in the last compartment/ tank of the system. The membrane module itself consists of flat sheet membranes arranged in a cartridge. A high mixed liquor suspended solids concentration in the aeration zone provides biological treatment and nitrification. The final effluent or permeate is pulled out by the permeate pump through the MBR membranes leaving behind large organic and inorganic particles for further digestion or wasting.

If nitrogen removal is not needed the system consists of a tank with two compartments or two separate tanks. The first compartment or tank provides primary treatment - sedimentation and separation of floatables and solids, and is equipped with an outlet screening device called SaniTEE®. From this screened compartment or tank, the wastewater will flow into the second compartment or tank, which is the aeration/membrane zone.



If nitrogen removal is needed the system consists of a tank with three compartments, or two tanks totaling at least three compartments, with exactly two compartments in the second or final tank. The first compartment or tank provides primary treatment - sedimentation and separation of floatables and solids, and is equipped with an outlet screening device called SaniTEE®. The second and third compartments must be in the same tank, and the second compartment is where denitrification takes place under anoxic conditions. The third compartment, the aeration/membrane zone, is separated from the anoxic zone by a baffle wall between the two zones to allow nitrified waste to enter into the anoxic area for denitrification.

NSF Standard 350 Class R Restricted Indoor Urban Reuse Water

The BioBarrier® system has been tested under NSF Standard 350 Class R (Residential) and is capable of treating residential wastewater for restricted indoor urban water reuse, which is toilet and urinal flushing. The system design requires a holding tank and plumbing system for reuse water and shall meet all applicable codes; have proper backflow prevention and protection against cross connections; and is the responsibility of the local designer/installer. When the reuse water is used for toilet and urinal flushing, additional disinfection should be considered to provide adequate assurance in preventing microorganism growth in the treated reuse water storage tank and as required by applicable codes.

The reuse tank shall be located after the BioBarrier® system. This tank shall also incorporate an overflow that allows excess reuse water to be dispersed in a locally approved soil dispersal system or released into a sanitary sewer system. A potable water make up system shall also be available to supply water when treated reuse water is not available. This potable water make up system shall include a properly designed backflow preventer that meets all applicable codes.

NSF Standard 350 Class R Unrestricted Outdoor Urban Reuse Water

The BioBarrier® system has been tested under NSF Standard 350 Class R (Residential) and is capable of treating residential wastewater for unrestricted outdoor urban water reuse, which is acceptable for use in surface and subsurface irrigation, including irrigation of edible crops without the edible portion being in direct contact with the treated water. A reuse tank may be required if the irrigation system requires it. The holding tank and plumbing system for reuse water shall meet all applicable codes; have proper backflow prevention and protection against cross connections; and is the responsibility of the local designer/installer. Additional disinfection should be considered to provide adequate disinfection to prevent microorganism growth in the treated reuse water storage tank and as required by applicable codes.

If a reuse tank is required for irrigation, it shall be located after the BioBarrier® system. This tank shall also incorporate an overflow that allows excess reuse water to be dispersed in a locally approved soil dispersal system or released into a sanitary sewer system. If a potable water make up system is required for irrigation, it shall include a properly designed backflow preventer that meets all applicable codes.

ONGOING SERVICE



WARNING

DO NOT ENTER THE SEPTIC TANK. Hazards exist in a septic system. All precautions must be followed when inspecting the system. Keep tank openings covered at all times. Only authorized service personnel should service a septic system. Lethal gases, high voltage electricity, and other deadly hazards associated with the system.



WARNING

Only qualified service staff should open access ports and/or covers. Infectious organisms exist in a septic tank. If any contact with wastewater, immediately wash and disinfect all exposed areas and contact personal physician. Failure to do so could result in severe sickness or death.

The BioBarrier® wastewater treatment system operates automatically and continuously. See SERVICE MANUAL for proper maintenance procedures for the user of the BioBarrier® wastewater treatment system include keeping the vents and the blower housing clear of debris. The homeowner should monitor the status of the system, substances introduced into the system, and the frequency of required pump-out as determined by the service provider.

A general evaluation of a BioBarrier® system's performance can be made using some simple observations which are outlined in the "Trouble Shooting" guide below. Normal operation of the system would include the following:

NORMAL OPERATING CONDITIONS	
SOUND	The BioBarrier® system's blower makes a constant humming noise, much like a household refrigerator. Under normal conditions, the blower should last 5+ years without need for replacement. If an unusual noise is heard, refer to the Trouble-Shooting Guide .
SMELL	A musty, earthy-type of odor is normal. However, if a sewage odor (rotten egg smell) is detected, refer to the Trouble-Shooting Guide .
SIGHT	A properly loaded and operated BioBarrier® system will produce effluent that looks like tap water. If the effluent is turbid, opaque, or suddenly changes, refer to the Trouble-Shooting Guide .

INTRODUCING SUBSTANCES INTO THE SYSTEM: While the FAST® wastewater treatment system will process most waste produced by the average household, introducing large amounts of substances into the system may reduce the efficiency of the system or stop the treatment process by destroying the biomass. These substances can be grouped as: prohibited substances and limited-use substances. Please refer to the "*DO'S AND DON'TS*" list to get familiar with *What You Can Put Down the Drain* to maximize the system's efficiency and reduce the time period between septic tank pump-outs.

IN GENERAL: If a substance is harmful to humans or is antibiotic in nature, it should not be put into any septic system - including BioBarrier®. If you have a question regarding the effect of a particular substance on the BioBarrier® system, call your Bio-Microbics service technician

ONGOING SERVICE

Continual service (or extended service for NSF certified systems beyond the first two years) is available and may be purchased

through your local Bio-Microbics distributor or current service provider. This service policy should provide the same services as the initial NSF service policy, and perform any additional service that may be required by local regulation.

SEASONAL/INTERMITTENT USE PROPERTIES

The BIOBARRIER® wastewater treatment system will function normally even if wastewater does not enter the system for an extended period of time. The power to the system should be left on during short periods when there is no wastewater flow to the system. Suggestions for intermittent use (Check with local regulations before attempting): If the property is going to be used seasonally and shut down completely for an extended period of time (e.g. summer use only and then abandoned for the winter), we suggest that the BioBarrier system be shut down. The system should be re-started upon return to the property. Your local service provider may be contacted to perform this operation. If the property will be used on weekends only, it is best to leave the system ON continuously throughout the season for use until an extended period of absence is anticipated (extended period being at least 3 weeks or more). A slight odor may be detected for a couple of days while the system returns to normal operation.

DO'S AND DON'T'S – What can I put down the drain?

Please refer to the list below for important information on how to help keep your treatment system performing as it should. Regular Maintenance should be performed by a qualified service company for ensuring the long life of your system.

DON'T PUT THESE ITEMS DOWN THE DRAIN

FOOD WASTES

ANIMAL BONES / EGG SHELLS
COFFEE GROUNDS / CORN COBS
FRUIT PEELS & RINDS
SKIN / HOME BREWERY WASTE

PERSONAL CARE PRODUCTS

BANDAGES / CONDOMS
DISPOSABLE DIAPERS
SANITARY NAPKINS
WET WIPES

CHEMICALS/TOXINS

AUTOMOTIVE FLUIDS
CAUSTIC CLEANERS
HARSH DETERGENTS
FLOOR STRIPPER
HERBICIDES / PESTICIDES
MEDICATIONS / DRUGS
PAINTS - OIL-BASED
QUATERNARY AMMONIA
SOLVENTS / THINNERS

OTHER PRODUCTS

CAT LITTER
CIGARETTE BUTTS
CLOTH TOWELS / RAGS
FILM DEVELOPING WASTE
METAL / PLASTIC OBJECTS
MODELING CLAY
PAPER TOWELS / SCRAPS
PLASTIC BAGS
RV WASTE
STRING / YARN / NYLON
STICKS / YARD WASTE

RECORD KEEPING

Keep copies of all system drawings/plans of the site/installed equipment/service records with all other home appliance documents. **Record all applicable information.**

LAUNDRY/WATER USAGE

Spread wash loads throughout the week. Instead of liquid fabric softener, dryer sheets should be used. Use low-suds, biodegradable and low phosphate detergents, like **Mighty Mike®** from **Scienco/FAST** (www.sciencofast.com).

LEAKY FIXTURES

Large quantities of water are added to your wastewater system when you have leaking fixtures. Timely detection and repair can help to maximize the life of your system, especially the drain field.

WATER SOFTENERS

The process may tolerate discharge from properly operating softeners that backwash as needed based on water usage (DIR) vs. timer operated systems, if allowed by your local regulatory authority. However, these discharges can possibly damage other parts of the septic system.

FOOD WASTES

Garbage disposal waste is acceptable - if allowed by your local regulatory authority. However, it may lead to more frequent removal of solids from your septic tank. For large quantities of food, please dispose of in the garbage.

FATS, OILS, & GREASE

Be aware grease (i.e. animal fats, vegetable oils, lard, etc) down the drain may overload or prevent the bacteria from fully breaking down the waste.

DRAINS FROM GARAGE/WORKROOMS

Should be diverted away from your septic system. Items like petroleum-based oils, gas, and saw dust should never enter the system.

DISINFECTANTS / CLEANERS

Use citric acid, chlorine, and/or other biodegradable cleaners according to the manufacturer's recommendations. Products containing quaternary ammonia or pine oil-based cleaners should not be used. Use drain cleaners as a last resort to unclog pipes.

MEDICINES

DO NOT FLUSH THEM DOWN ANY DRAIN. All antibiotic medicines are harmful to treatment quality. Unused medications should be returned to the pharmacy, doctor, or thrown away in the trash.

NOTE: As the human body absorbs $\leq 20\%$ of these medications, please notify your service provider of medicines in the house. This could reduce troubleshooting efforts and possibly your maintenance bill.

SEPTIC TANK ADDITIVES / ENZYMES

The wastewater in the system contains all the required bacteria for proper operation. Additives are unnecessary; and may do more harm than good.

PAPER PRODUCTS

Use single- or double-ply, non-quilted, white toilet paper products. Some color dyes in the paper cannot be eaten by natural bacteria. Non-bleached paper (brown in color) takes longer to break down and can therefore increase your biosolids pump out frequency. Avoid flushing paper towels, napkins, wipes, or other thicker paper material.

PLEASE BE AWARE OF THE FOLLOWING - failure to do so could result in severe sickness or death:

- Only qualified service persons should open any access port on a septic system. Always secure all access covers of the tank, control panel and blower, so that people cannot enter without the use of proper tools.
- Gases emanating from septic tanks can explode if ignited and is deadly if inhaled. DO NOT use flame or spark near a septic tank access points and never enter the septic tank.
- Infectious organisms exist in a septic tank. Persons coming in contact with wastewater must immediately wash and disinfect all exposed areas and contact their personal physicians.

DO'S AND DONT'S – in the yard

WARNING


Always secure all access covers in place so that people cannot enter the tank, control panel or blower without the use of proper tools. DO NOT use flame or spark near a septic tank's access points. Gasses emanating from septic tanks can explode if ignited or deadly if inhaled.

Only qualified service persons should open any access port or cover on the system. Hazards such as electric shock and Infectious organisms exist in these areas.

Persons coming in contact with wastewater, must immediately wash and disinfect all exposed areas and contact your personal physician. Failure to do so could result in severe sickness or death.

BLOWER OPERATION

DO NOT turn off the blower for periods longer than 30 minutes. Treatment quality and drain field life could be reduced. If the blower appears to be functioning improperly, reference the Trouble Shooting guide in this manual. If the property is being vacated for an extended period (> 3 weeks), see the section of this manual titled "Intermittent Use".



DOWN SPOUTS

Anywhere water is collected, i.e. roof downspouts, pavement runoff, or sump pump/house footing drains, the water should be diverted away from the septic tank or drainfield.

TRAFFIC / LANDSCAPING




Do not drive over any portion of your system (tank, piping, drain field) except for normal yard traffic, i.e. lawn mowers, etc. Tanks (H-20) can be made for under roadways, driveways. If possible, deter traffic by using a fence or create a landscaped area with shallow root plants (ornamentals, bushes, decorative grasses, and/or flowers). Don't plant trees near any portion of your system (within 30').

ALARM

The alarm may be silenced using the "RESET" button on the panel's front. Service assistance may be obtained from the local Bio-Microbics distributor or Bio-Microbics, Inc. Information located on the control panel labels may be required to obtain accurate assistance.

VENTS / INTAKES

Keep the BioBarrier® system's vent clear of debris such as leaves and snow. Do not allow the blower housing louvers to become blocked with any debris. Clean the blower's inlet filter at least annually.



STRUCTURES

Do not build patios, carports, or other structures over any part of your septic system; as this may cause damage.

BIOSOLIDS (SLUDGE) REMOVAL

To determine when pump out is required; a maintenance provider should measure the biosolids in the tank(s) on a regular basis. Please see the service manual for specific procedures.



NSF INTERNATIONAL CERTIFIED SYSTEMS SERVICE POLICY

All NSF (National Sanitation Foundation)/ANSI Standard 40 Class 1 / Standard 245 / Standard 350 Class R certified wastewater treatment systems (BioBarrier® 0.5, 0.5-N, 1.0, 1.0-N, 1.5, and 1.5-N) have an initial two-year service agreement included with the system's initial purchase price (two service calls per year). The NSF service calls **ONLY** cover NSF certified systems; other components of the septic system are **NOT** covered.

If there are any deficiencies in the BioBarrier® system's operation or components, the service person will notify the owner in writing and detail when these deficiencies can be fixed.

The company listed on the blower housing or control panel label performs this service. During an NSF service call, the service company shall inspect the blower for proper operation, visually inspect the system's effluent for clarity, clean the blower air filter and assure proper function of the control panel. If these service calls are not performed on your NSF certified system, or not all of the items are checked, please call Bio-Microbics at: **800-753-FAST(3278) or (913)422-0707**

For continual service of NSF certified systems beyond the first two years, an extended service agreement is available through your local Distributor or current service provider. This policy should provide the same services and may include any additional services that are required by local regulation.

LIMITED WARRANTY

Bio-Microbics, Inc. warrants every new residential BioBarrier® system against defects in materials and workmanship for a period of two years after installation or three years from the date of shipment, subject to the following terms and conditions, and commercial BioBarrier HSMBR® system for a period of one year after installation or eighteen months from date of shipment, whichever occurs first, subject to the following terms and conditions:

During the warranty period, if any part is defective or fails to perform as specified when operating at design conditions, and if the equipment has been installed and is being operated and maintained in accordance with the written instructions provided by Bio-Microbics, Inc., Bio-Microbics, Inc. will repair or replace at its discretion such defective parts free of charge. Defective parts must be returned by owner to Bio-Microbics, Inc.'s factory postage paid, if so requested. The cost of labor and all other expenses resulting from replacement of the defective parts and from installation of parts furnished under this warranty and regular maintenance items such as filters or bulbs shall be borne by the owner. This warranty does not cover general system misuse, aerator components which have been damaged by flooding or any components that have been disassembled by unauthorized persons, improperly installed or damaged due to altered or improper wiring or overload protection. This warranty applies only to the treatment plant and does not include any of the house wiring, plumbing, drainage, septic tank or disposal system. Bio-Microbics, Inc. reserves the right to revise, change or modify the construction and/or design of the BioBarrier® system, or any component part or parts thereof, without incurring any obligation to make such changes or modifications in present equipment. Bio-Microbics, Inc. is not responsible for consequential or incidental damages of any nature resulting from such things as, but not limited to, defect in design, material, or workmanship, or delays in delivery, replacements or repairs.

THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED. BIO-MICROBICS SPECIFICALLY DISCLAIMS ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

NO REPRESENTATIVE OR PERSON IS AUTHORIZED TO GIVE ANY OTHER WARRANTY OR TO ASSUME FOR BIO-MICROBICS, INC., ANY OTHER LIABILITY IN CONNECTION WITH THE SALE OF ITS PRODUCTS.

Contact your local distributor for parts and service.

SERVICE AFTER THE FIRST TWO YEARS

An Extended Service Policy is available and may be purchased through your local Bio-Microbics distributor. The extended service policy should provide the same service checks as the initial NSF service policy, sludge accumulation levels in the septic and FAST tanks, and perform any additional service required by local regulation. Extended service on NSF certified systems should be performed twice per year.

Keep for Your Records



BioBarrier ID Serial Number: _____

System Designer Name: _____

Designer Phone: _____

Health Official Name: _____

Health Official Phone: _____

Manufacturer Name: Bio-Microbics, Inc.

Manufacturer Phone: 1-800-753-FAST (3278)

Installed By: _____

Installer Phone: _____

Maintenance Provider Name: _____

Maintenance Provider Phone: _____



BETTER WATER. BETTER WORLD.®

8450 Cole Parkway • Shawnee, Kansas 66227 USA

(o) 913-422-0707 • (f) 913-422-0808 • 800-753-3278 (FAST)

www.biomicrobics.com • sales@biomicrobics.com